

Redneck Autocross — Vehicle Inspection Requirements

Radiator, Fuel & Battery

- Radiators may be relocated to the rear of the vehicle, but must be rigidly mounted to prevent coming loose or disconnecting.
- Stock fuel tanks may be removed and replaced with an alternative fuel cell. Fuel cells must be mounted safely.
- All electrical wiring must be routed away from any relocated fuel cell to prevent the risk of combustion.
- Front oil pan and radiator shielding are permitted.
- The battery must be secured and covered.

Suspension & Drivetrain

- Stock suspension only. Performance shocks, geometry changes, and altered mounting locations are not permitted. Reinforcing existing suspension is allowed.
- 4WD trucks — front driveshaft must be removed.
- 4WD cars — the rear driveshaft must be removed.

Tires & Mudflaps

- Any street-legal or DOT-approved tires are permitted.
- Air inflation only.
- Tire beads may be screwed to rims.
- Split rims are not permitted.
- Mudflaps are not required but strongly encouraged.

Bumpers & Airbags

- Bumpers must be similar to stock with no sharp edges or overbuilt construction.
- All airbags must be fully removed — including roof bags. Removing the fuse is not sufficient, as airbags can still deploy. Full removal is required.

Doors

- Doors must remain closed and on the vehicle at all times.
- All doors must be heavily duct-taped or zip-tied shut to allow emergency access by the fire department.
- Door bars are permitted.

General Requirements

- Hood must be secured against opening during racing.
- The vehicle must have a tow point on both the front and rear.

- Hood must be accessible quickly in the event of an emergency.
- Vehicle numbers must be vertical, clear, and legible on both sides of the vehicle and on the roof, readable from both sides.
- All loose items must be removed from the vehicle's interior and exterior before arriving at the track.

Roll Cage: A full roll cage with a halo, or a four-point roll cage welded or bolted securely, is strongly encouraged but not required.